

BIPRO

TP7G54M TP7G54M(H) **108-cell**

390 - 410W

Bifacial Module With Transparent Backsheet 10BB Half-cut Mono Perc

SYSTEM & PRODUCT CERTIFICATES



Linear Performance Warranty

- IEC 61215 / IEC 61730 / UL 61703
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems







PERFORMANCE WARRANTY









Excellent Anti-PID Perform
2 times of industry standard Anti-PID t



Lower LC0E

2% more power generation, lower LCOE



P68 Junction Box ligh waterproof level

REAR SIDE POWER GAIN(REFERENCE TO 410W FRONT)

Pmax gain	5%	10%	15%	20%	25%
Pmax/W	431	451	472	492	513
Vmpp/V	31.43	31.43	31.43	31.43	31.43
Impp/A	13.70	14.36	15.01	15.66	16.31
Voc/V	37.50	37.50	37.50	37.50	37.50
Isc/A	14.65	15.35	16.04	16.74	17.44

I-V CURVE

— 1000W/m² — 800W/m² — 600W/m² — 400W/m² — 200W/m² Voltage (V)

APPLICATION CONDITIONS

Maximun System Voltage	1000V/1500V/DC	
Operating Temperature	-40°C~+85°C	
Maximun Series Fuse	30A	
Safety Protection Class	Class	
Mechanical Load	Front side 5400Pa, Back side 2400Pa	
Refer. Bifaciality Factor	70%+5%/-10%	

— 75°C — 50°C — 25°C Voltage (V)

TEMPERATURE CHARACTERISTICS

Temperature Coefficient of Pmax	
Temperature Coefficient of Voc	
Temperature Coefficient of Isc	
Nominal Module Operating Temperature(NMOT)	

PACKING CONFIGURATION

Pieces Per Pallet	
Pieces Per Container(40'HQ)	

TECHNICAL DRAWINGS

