



# BISTAR

TP7F72M  
TP7F72M(H) **144-cell**

530 - 550W

10BB PERC



10BB

2%

0.55%



PID

PID  
85 /85% RH 192



IP68

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015 质量管理体系
- ISO 14001: 2015 环境管理体系
- ISO 45001: 2018 职业健康安全管理体系



12

25

100%

98%

保证功率

84.8%

5

12

15

20

25

[www.talesun.com](http://www.talesun.com)

[marketing.hq@talesun.com](mailto:marketing.hq@talesun.com)

\* GL-EN-Version 2024.03.22

	STC	NMOT	\$
	530	395	\$
	41.32	38.6	4
	12.83	10.24	1
	49.32	46.4	4
	13.72	11.06	1
	20.50		

	NMOT	STC	NMOT
	406	550	410
	39.0	41.96	39.1
	10.41	13.11	10.47
	46.8	49.92	47.0
	11.23	14.00	11.28
	21.10		21.30

	10BB
	144 (6*24)
	2278*1134*35mm (89.69*44.65*1.38 )
	28kg (61.73lbs.)
	3.2mm
	IP68, 3
	4mm <sup>2</sup> (IEC), 12AWG(UL 350mm(+),250mm(-)
	T01/LJQ-3-CSY/MC4/M

	1000V/1500V/DC
	-40°C~+85°C
	25A
	Class

	31	
	620	

